

FABRICANTES DE EXPRIMIDORES DE CÍTRICOS

MANUFACTURERS OF CITRUS JUICERS

Exprimidor profesional de cítricos

Professional citrus juicers.

ACID2 EVOLUTION

ABS

COLLECTION ACID





TECHNICAL CHARACTERISTICS

Voltage:230V / 220V / 110V Frequency: 50Hz / 60Hz

Phases: 1(monophase)
RPM: 1.300 / 1.600

Current: 2,8A / 6,2A

Capacitor: 10nf / 40nf Power: 0,50Hp / 570W Protection rating: IP21

Motor supplied with thermal protector

Maximum operating time: 30min.

Stop/start standard version: automatic

Dimensions width x length x height: 330 x 350 x 430 mm

Weight: 15.5 kg

Diseñado bajo directiva 89/392 CE.






















HROME SILVER CHROME GC









MAIN ATTRIBUTES

Lever system (standard) - Lever in unbreakable material - Bodywork constructed of anti-scratch material. Orange coloured finish - Easy to clean bodywork (without corners/ridges) - Internal components in (304) stainless steel - Automatic start system at the press of the lever - Rapid access cleaning system for internal parts - All components can be washed in a dishwasher at 90°C - Incorporated juice glass made of unbreakable material - Motor sized so as not to raise the internal temperature of the machine (always squeezing the oranges at room temperature).

Optional: Bodywork in ABS white snow colour or in anti-corrosion material with silver or gold chrome finish.

