

FABRICANTES DE MOLINOS DE CAFÉ

MANUFACTURERS
OF COFFEE GRINDERS

Molino de café profesional para todo tipo de cafés

Professional coffee grinder for all types of coffee.

KENIA "63dB"

COLLECTION SILENCER



TECHNICAL CHARACTERISTICS 0-500gr/6' Max 2Kg

Voltage: 230V / 220V / 110V
Frequency: 50Hz / 60Hz
Phases: 1(monophase)

RPM: 1.300 / 1.600

Current: 1,75A / 3,7A
Capacitor: 10nf / 40nf

Power: 0,20Hp / 356W Protection rating: IP21

Motor supplied with thermal protector

Maximum operating time: 30 min.

Tempered steel grinding wheel (62HRc) Ø 60mm

Lifespan of grinding wheels: 500kg

Hopper capacity: 1kg

Doser capacity: 300g

Doser regulation: 5/12g

Doser lever: right/left

Stop/start standard version: automatic

Dimensions width x length x height: 210x380x510mm

Weight: 11kg

Air noise: 63dB


Diseñado bajo directiva 89/392 CE.


















INO)









MAIN ATTRIBUTES

Hopper (1kg) made of unbreakable and non-deformable material (co.polyester), with fast lock system and self-levelling when off the coffee grinder, with the possibility of cleaning in a dishwasher at 90 °C. Micrometric regulation of the coffee grind using a regulatory pawl. New expulsion system for the ground coffee (always leaving the grinding cavity clean when the coffee grinder stops). Bodywork made of stainless steel, with ventilation system (internal air inlet and outlet). Large tray integrated into the body, ready to take knocks (portafilter). Single-bodied, hermetically sealed doser without aroma loss, vibrationless and made of unbreakable material. Ergonomic handle. Universal coffee tamper (rotatable). Doser fitted with gasket-saver (portafilter positioner). Hardened steel grinding blades (62/65 HRc) 60mm in diameter. Motor assembly with anti-vibration system. Silencer motor with internal autoventilation, 63dB.

Optional: Left- or right-handed doser lever. Coffee counter. Optional personalisation system with chrome plates on the doser and on the rear of the bodywork.